
## 40W X 2 Solar Street Light

## Model - SFSOLST40X2UNI-LI



The Sunfor Universal Solar street light is slimline, compact and aesthetically pleasing which incorporates all components together in modern and robust design. This model is supplied with a 40w Litup COB LED with a lumen output of 151lm/w.

5Hrs 100%, 8Hrs 70%

Distribution is an Asymmetrical batwing design.

The battery is designed for 13Hrs with 2 nights of reserve and requires 5 hours to replenish.

Each model is supplied with lasercut lettering into the cradle which can be used to highlight, name of place, street / road or place of interest.

Lithium Ferro Phosphate Lifepo4 battery with an 8 year life cycle.

Different luminaire options with multiple lens configurations





## **Model - SFSOLST40X2UNI-LI**

	D	40111110
	Power	40W X 2
1 1	LED	Litup
	IP Rating	IP 65
LIGHT	Flux @ CCT 5700 - 6000K	6040lm X 2
	CRI - Colour Rendering Index	80
	Optical control	Glass Lens
LIGITI	Average Lifespan	8 years
	Operating temperature	-30 Deg ~ + 45 Deg
	Mounting height	7 meter above surface
	Beam angle	Assymetrical batwing 140 x 80
	Lumen per watt	151
	Pole to pole distance	35 meters
BATTERY	Lithium Ferro Phosphate	Sharp
	Voltage	25.6v
BATTERT	Watt Hours	1732Wh
	Lifespan	2000 cycles
SOLAR	Power	300w
PANEL	Voltage	36v
TAREE	Maximum current	8.72Amp
	Charging method	MPPT
	Dimming parameters	100 / 70 / 50 & 30%
CONTROLLER	Day night sensor	Integrated Day / Night sensor
	Lighting parameters	4 stage programmable
		Temperature compensation
	Electrical parameters	Overheating, overcharging and
		over discharging protections
BATTERY CRADLE AND ENCLOSURE	Aluzinc and powder coated Manufactured in an SABS approved facility with ISO 9001 3CR12 Stainless steel optional	
POLE	Galvanized with an option to powder coat - 8m (127 - 114mm collar)	
WARRANTY	3 years on all components - option to extend	

